



Njesite Outdoor DC Inverter

GMV 5										
Modeli		GMV-224WM/B-X	GMV-280WM/B-X	GMV-335WM/B-X	GMV-400WM/B-X	GMV-450WM/B-X	GMV-504WM/B-X	GMV-560WM/B-X	GMV-615WM/B-X	
Gama e kapacitetit		HP	8	10	12	14	16	18	20	22
Kapaciteti	Ftohje	Kw	22.4	28	33.5	40	45	50.4	56	61.5
	Ngrohje	kW	25	31.5	37.5	45	50	56	63	69
EER		W/W	4.31	4	3.98	3.76	3.56	3.55	3.5	3.32
COP		W/W	4.55	4.32	4.17	4.05	3.85	4.01	3.8	3.65
Furnizimi me energji		Ph/V/Hz	380~415V-3Ph-50/60Hz							
Intensiteti i rrymes		A	15.7/20	20.9/25	24.7/32	28.8/40	33.2/40	44.7/5	50/63	52/63
Konsumi i energjise	Ftohje	kW	5.2	7	8.41	10.65	12.65	14.2	16	18.5
	Ngrohje	kW	5.5	7.3	9	11.1	13	14.1	16.6	18.9
Nr. Max i Indooreve		njesi	13	16	19	23	26	29	32	35
Volumi i ngarkeses se gazit		Kg	5.9	6.7	8.2	9.8	10.3	11.3	14.3	14.3
Niveli i presionit te zhurmes		dB(A)	60	61	63	63	63	63	63	64
Lidhja e tubit	Likuid	inch(mm)	ø9.52	ø9.52	ø12.7	ø12.7	ø12.7	ø15.9	ø15.9	ø15.9
	Gaz (presion i ulet)		ø19.05	ø22.2	ø25.4	ø25.4	ø28.6	ø28.6	ø28.6	ø28.6
Dimensionet (LxGjxTh)	E jashtme	mm	930x765x1605	930x765x1605	1340x765x1605	1340x765x1605	1340x765x1605	1340x765x1740	1340x765x1740	1340x765x1740
	Paketimi	mm	1010x840x1775	1010x840x1775	1420x840x1775	1420x840x1775	1420x840x1775	1420x840x1910	1420x840x1910	1420x840x1910
Pesha		Kg	235	235	300	375	375	375	400	400

Funksioni	Kushtet nominale operative (temperatura)				Gama e operimit (temperatura)
	Kushtet outdoor		Kushtet indoor		Kushtet outdoor DB(°C)
	DB(°C)	WB(°C)	DB(°C)	WB(°C)	GMV5
Ftohje	35	0	27	19	-5~52
Ngrohje	7	6	20	0	-20~24